

INDUSTRIAL OPEN TOP ROLL-OFF CONTAINER



SPECIFICATIONS

SIDES ... 10 GUAGE FLOOR ... 3/16"

UNDERSTRUCTURE ... 3" STRUCTURAL CHANNEL

SPACING ... 15" ON CENTER, GUSSETED 30" CTR

LONG SILLS ... 6" X 2" X 1/4" TUBE TOP RAIL ... 4" X 3" X 1/8" TUBE

UPRIGHTS ... 3" X 5" X 3" W/ 24" ON CENTER

HOOK PLATE ... 3/4" HOOK PLATE W/ 11/4" GRAB HOOK

FRONT CORNER POST ... 6" X 6" X 10GA

WHEELS ... 8" X 10" STEEL WHEELS

WHEEL AXLES ... 11/2" STANDARD W/ GREASE FITTINGS PAINT ... PPG ALKYD ENAMEL PRIMER & PAINT

LATCH SYSTEM ... HANDLE

OPTIONS

- INVERTED ANGLE
- PUSH PLATE
- INTERIOR CLEANOUT
- SEALED GATE
- SUMP
- RATCHET CATCH

PLEASE ASK YOUR SALES REP FOR ALL AVAILABLE OPTIONS

STANDARDS LISTED APPLY TO 20, 30, 40 YARD CONTAINERS

DURABLE. DEPENDABLE. DESIGNED FOR YOU.